



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/09/2020

 8.4
 08/06/2020
 1329735-00040
 Date of first issue: 02/27/2017

SECTION 1. IDENTIFICATION

Product name : Freon™ 123 (R-123) refrigerant

SDS-Identcode : 130000024258

Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street

Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-

773-2000); Transport emergency: +1-800-424-9300 (outside

the U.S. +1-703-527-3887)

Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant

Restrictions on use : For professional and industrial installation and use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Specific target organ toxicity

- single exposure

Category 3

GHS label elements

Hazard pictograms :

<u>(!)</u>

Signal Word : Warning

Hazard Statements : H336 May cause drowsiness or dizziness.

Precautionary Statements : Prevention:


P261 Avoid breathing mist or vapors.

P271 Use only outdoors or in a well-ventilated area.

Response:

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel

unwell.





Version **Revision Date:** SDS Number: Date of last issue: 05/09/2020 08/06/2020 1329735-00040 Date of first issue: 02/27/2017 8.4

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Dangerous for the ozone layer.

Vapors are heavier than air and can cause suffocation by reducing oxygen available for breathing. Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Substance

Substance name 2,2-Dichloro-1,1,1-trifluoroethane

CAS-No. 306-83-2

Components

Chemical name	CAS-No.	Concentration (% w/w)
2,2-Dichloro-1,1,1-trifluoroethane	306-83-2	100

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Get medical attention if symptoms occur.

In case of eye contact Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

May cause cardiac arrhythmia.

Inhalation of high concentration may cause

Anaesthetic effects

Dizziness confusion

Light-headedness





Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Drowsiness Unconsciousness Irregular cardiac activity

fainting Weakness

Skin contact may provoke the following symptoms:

Irritation Discomfort Pain

Swelling of tissue

Rash Itching

Eye contact may provoke the following symptoms

Discomfort Pain Redness

Impairment of vision

Adverse effects from repeated inhalation may include

Liver disorders

May cause drowsiness or dizziness.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Because of possible disturbances of cardiac rhythm, ca-

techolamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with spe-

cial caution.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Not applicable

Will not burn

Unsuitable extinguishing

media

Not applicable Will not burn

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Freon™ 123 (R-123) refrigerant



Version 8.4

Revision Date: 08/06/2020

SDS Number: 1329735-00040 Date of last issue: 05/09/2020 Date of first issue: 02/27/2017

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Avoid breathing mist or vapors. Advice on safe handling

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet

piped to use point.

Use a check valve or trap in the discharge line to prevent ha-

zardous back flow into the cylinder.

Use a pressure reducing regulator when connecting cylinder

to lower pressure (<3000 psig) piping or systems.

Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement.

Take care to prevent spills, waste and minimize release to the

environment.

Freon™ 123 (R-123) refrigerant



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 05/09/2020

 8.4
 08/06/2020
 1329735-00040
 Date of first issue: 02/27/2017

Conditions for safe storage : Cylinders should be stored upright and firmly secured to pre-

vent falling or being knocked over.

Separate full containers from empty containers.

Do not store near combustible materials.

Avoid area where salt or other corrosive materials are present. Do not expose drums to direct heat or temperature above 46°C (115°F) to avoid pressurizing and possibly distorting the

drums.

Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage

the exposure.

Keep in properly labeled containers.

Store locked up.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage tem-

perature

< 126 °F / < 52 °C

Storage period : > 10 y

Further information on stor-

age stability

: The product has an indefinite shelf life when stored properly.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2,2-Dichloro-1,1,1- trifluoroethane	306-83-2	TWA	50 ppm	US WEEL

Engineering measures : Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied





Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate

protection.

Hand protection

Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : slight, ether-like

Odor Threshold : No data available

pH : 7

Melting point/freezing point : No data available

Initial boiling point and boiling


range

82.0 °F / 27.8 °C

Flash point : does not flash

Evaporation rate : < 1

(CCL4=1.0)





Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Will not burn

Upper explosion limit / Upper

flammability limit

Upper flammability limit Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit

Method: ASTM E681

None.

Vapor pressure : 913.6 hPa (77 °F / 25 °C)

Relative vapor density : 5.5

Relative density : 1.47 (77 °F / 25 °C)

Density : 1.46 g/cm³ (77 °F / 25 °C)

(as liquid)

Solubility(ies)

Water solubility : 3.9 g/l (77 °F / 25 °C)

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known.

Incompatible materials : None.

Freon™ 123 (R-123) refrigerant



Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Acute oral toxicity : LD50 (Rat): 9,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 32000 ppm

Exposure time: 4 h Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 20000

ppm

Symptoms: Cardiac sensitization

No observed adverse effect concentration (Dog): 10000 ppm

Symptoms: Cardiac sensitization

Cardiac sensitisation threshold limit (Dog): 124,000 mg/m³

Symptoms: Cardiac sensitization

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Species : Rabbit

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Species : Rabbit

Freon™ 123 (R-123) refrigerant



Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Routes of exposure : Skin contact Species : Guinea pig Result : negative

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Germ cell mutagenicity - : Weight of evidence does not support classification as a germ

Assessment cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Carcinogenicity - Assess- : Weight of evidence does not support classification as a car-

ment cinogen, Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

sessment

2,2-Dichloro-1,1,1-trifluoroethane:

Reproductive toxicity - As- : Weight of evidence does not support classification for repro-

ductive toxicity

Freon™ 123 (R-123) refrigerant



Version **Revision Date:** SDS Number: Date of last issue: 05/09/2020 08/06/2020 1329735-00040 Date of first issue: 02/27/2017 8.4

STOT-single exposure

May cause drowsiness or dizziness.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Assessment May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Assessment No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

Repeated dose toxicity

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Species Rat **NOAEL** 3.13 mg/l LOAEL : 6.3 mg/l

Application Route : inhalation (vapor)

Exposure time 70 d

Remarks No significant adverse effects were reported

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 55.5 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 17.3 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 96.6

mg/l

Exposure time: 96 h

EbC50 (Pseudokirchneriella subcapitata (green algae)): 67.8

mg/l

Exposure time: 96 h

Freon™ 123 (R-123) refrigerant



Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Persistence and degradability

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 24 % Exposure time: 28 d

Bioaccumulative potential

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Bioaccumulation : Bioconcentration factor (BCF): 33

Mobility in soil

No data available

Other adverse effects

Components:

2,2-Dichloro-1,1,1-trifluoroethane:

Ozone-Depletion Potential : 0.02

Where a range of ODPs is indicated, the highest value in that range shall be used for the purposes of the Protocol. The ODPs listed as a single value have been determined from calculations based on laboratory measurements. Those listed as a range are based on estimates and are less certain. The range pertains to an isomeric group. The upper value is the estimate of the ODP of the isomer with the highest ODP, and the lower value is the estimate of the ODP of the isomer with the lowest ODP.

Regulation: UNEP - Handbook for the Montreal Protocol on Substances that Deplete the Ozone Layer (Update: 2016-11-

23)

Group: Annex C - Group I: HCFCs (consumption and produc-

tion)

0.02

Includes all isomers of the substance, regardless of whether

the isomer is explicitly listed on its own.

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class II

Substances (Update: 2007-07-01)

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Freon™ 123 (R-123) refrigerant



Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

2,2-Dichloro- 306-83-2 100 %

1,1,1-

trifluoroethane

US State Regulations

Pennsylvania Right To Know

2,2-Dichloro-1,1,1-trifluoroethane 306-83-2

International Regulations

Montreal Protocol : 2,2-Dichloro-1,1,1-trifluoroethane

Freon™ 123 (R-123) refrigerant




Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information.


For further information contact the local Chemours office or nominated distributors.

Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable





Version Revision Date: SDS Number: Date of last issue: 05/09/2020 8.4 08/06/2020 1329735-00040 Date of first issue: 02/27/2017

Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 08/06/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8