

Emkarate[®] RL 32H

Typical Properties Data Sheet

Product Description:

Emkarate RL 32H is an ISO VG 32 synthetic polyol ester (POE) lubricant formulated specifically for use in refrigeration and air-conditioning compressors using HFC refrigerants. This product provides effective wear protection for steel and aluminum surfaces for increased system life and improved efficiency and is suitable for both initial fill and service fill. The combination of low temperature characteristics and unparalleled chemical and thermal stability enable the use of Emkarate RL 32H over a wide operating temperature range.

| Analysis | Method | Typical Value |
|-------------------------|------------|---------------|
| Viscosity @ 40°C (cSt) | ASTM D445 | 32.5 |
| Viscosity @ 100°C (cSt) | ASTM D445 | 5.8 |
| Viscosity Index | ASTM D2270 | 121 |
| Pour Point (°C) | ASTM D97 | -46 |
| Density @ 20°C (g/ml) | ASTM D1298 | 0.977 |
| Flash Point COC (°C) | ASTM D92 | 258 |
| Acid Value (mg KOH/g) | ASTM D974 | <0.05 |

These values are not intended for use in preparing specifications. Additional technical information such as water content is available upon request.

North & South America
The Lubrizol Corporation
2300 James Savage Rd.
Midland, MI 48642, USA
Phone: 989-496-3780
Email: sales@cpieng.com

Europe, Middle East & Africa
Lubrizol Limited
Pavilion One, Belasis Court
Greenwood Road
Stockton-on-Tees
TS23 4AZ, UK
Phone: +44 1642 565266
Email: euafricamesales@cpieng.com

Asia-Pacific
Lubrizol Southeast Asia (Pte) Ltd
44 Tanjung Penjuru
Singapore 609032
Phone: +65-66638 684
Email: asiasales@cpieng.com

www.emkarateRL.com

www.cpieng.com